

NEW *Swing*

The curved cover of the Swing makes it a focal point in any room. And with a choice of colours to choose from you can make a real statement.



12 models

Heights: 1820 & 2020mm

Lengths: 504mm to 727mm

Outputs: 1224 to 2376 watts, 4176 to 8107 Btu/hr

Types: P+ & K2

For full details please refer to page 99

For colour options please refer to page 132

NEW Stelrad Swing

50 Δ t

P+

K2

Height	Emitter length mm	Casing length mm	UIN	Heat output Watts Btu/hr		Casing length mm	UIN	Heat output Watts Btu/hr	
1820	400	504	38418210	1224	4176	527	38418220	1476	5036
	500	604	38518210	1530	5220	627	38518220	1845	6295
	600	704	38618210	1836	6264	727	38618220	2214	7554
2020	400	504	38420210	1308	4463	527	38420220	1584	5405
	500	604	38520210	1635	5579	627	38520220	1980	6756
	600	704	38620210	1962	6694	727	38620220	2376	8107

40 Δ t

P+

K2

Height	Emitter length mm	Casing length mm	UIN	Heat output Watts Btu/hr		Casing length mm	UIN	Heat output Watts Btu/hr	
1820	400	504	38418210	863	2943	527	38418220	1040	3549
	500	604	38518210	1078	3679	627	38518220	1300	4437
	600	704	38618210	1294	4415	727	38618220	1560	5324
2020	400	504	38420210	922	3146	527	38420220	1116	3809
	500	604	38520210	1152	3932	627	38520220	1396	4762
	600	704	38620210	1383	4718	727	38620220	1675	5714

30 Δ t

P+

K2

Height	Emitter length mm	Casing length mm	UIN	Heat output Watts Btu/hr		Casing length mm	UIN	Heat output Watts Btu/hr	
1820	400	504	38418210	630	2151	527	38418220	760	2594
	500	604	38518210	788	2688	627	38518220	950	3242
	600	704	38618210	945	3226	727	38618220	1140	3890
2020	400	504	38420210	674	2298	527	38420220	816	2784
	500	604	38520210	842	2873	627	38520220	1020	3479
	600	704	38620210	1010	3447	727	38620220	1224	4175

EN 442 Certification Data – CETIAT tested in accordance with BS EN 442

Type	P+		K2	
	1820	2020	1820	2020
Height	1820	2020	1820	2020
W/m at 75/65/20	3060	3270	3690	3960
n-coefficients	1.30	1.30	1.33	1.33
Heated Surface Area (m ² /m)	13.58	16.20	29.90	37.74
Weight (kg/m)	96.00	106.20	105.30	116.40
Water Contents (l/m)	15.90	17.70	15.90	17.70
Wall to tap centre (mm)	65	65	77	77